TABLE 1
Summary of Soil Sample Analytical Methods

Sample Type	EPA Method	Analyte
Hot Spot Sample	418.1	TRPH (a)
-	6000/7000	Metals
	8260	VOCs
	8270	SVOCs
	8080	PCBs
	8015M	Fuel Characterization
Stockpile Sample	418.1	TRPH (a)
	6000/7000	Metals
	8260	VOCs
	8270	SVOCs
	8080	PCBs (b)
Confirmation Sample	418.1	TRPH (a)
_	6000/7000	Metals
	8260	VOCs (c)
	8270	SVOCs (c)
	8080	PCBs (d)
	8015M	Fuel Characterization (e)

## Notes:

TRPH Total Recoverable Petroleum Hydrocarbons

VOCs Volatile Organic Compounds

SVOCs Semi-volatile Organic Compounds.

PCBs Polychlorinated Biphenyls

- (a) Samples exhibiting TRPH concentration greater than 10,000 mg/kg were submitted for carbon chain analysis.
- (b) One sample per remedial excavation.
- (c) The number of confirmation samples analyzed for VOCs and SVOCs is approximately equal to the number of stockpile samples analyzed for VOCs and SVOCs. Confirmation samples are selected for analysis of VOCs and SVOCs based on highest TRPH concentration, and location of evenly spaced confirmation sample locations.
- (d) Generally, one sample per each remedial excavation, or following the removal of each 2500 cubic yards of soil, whichever is less.
- (e) Confirmation samples were selectively analyzed for fuel characterization.